

Section 7 Town 6 Range 5

Dec 20 1812

I commenced a Survey of Section 7, T. 6, R. 5  
for \_\_\_\_\_


Ransom W. Raper }  
Ulysses Heidigh } C. B. Sworn  
Richard Raper Jr. }  
W. W. Blosston  
Surveyor Greene County.

Var.

Course.	Point of Beginning.	Chains Distance.	Corrected Bearings.
South	A E	39.83	T. E 1/4
West	A E	39.99	to A 1/4
		84.66	" A 1/4
South	A W	79.80	" S W
East	S W	47.19	" S 1/4
North	S 1/4	39.83	" Cen

CORNER ESTABLISHED.	Monument.	Device.	WITNESS POINTS OR BEARING TREES.	Mark or Dia. in Inches.	COURSE.	Links Distant.	REMARKS.
Re est A E			N Oak	2 1/2	A 37 1/2 E	12 1/2	
			N Oak	2 1/2	A 60 E	15 1/2	
			Stone		A 61 W	10 1/2	
" E 1/4			N Oak	2 1/2	corner tree		
" S 1/4			S E cor of E header		S 36 E	4 1/2	
			S W cor of W header		S 12 1/2 W	3 1/2	
Cen 1/4	Concrete		Elm	3	A 49 E	2 1/2	
A 1/4 S W	Stone		Willow	8	A 31 W	6 1/2	
			Post		North	14 3/4	
E 1/4 S W	"		Sassafras	8	S 30 1/2 W	20 1/2	
			Post		West	11 1/2	
W 1/4 S W			Osage Orange	10	A 52 1/2 W	39	
			Concrete Post		East	30	
Cen S W			Hickory	12	A 14 1/2 W	38	
			"	10	A 9 1/4 W	44 1/2	
750 S of A 1/4 S W 1/4			Sassafras	8	A 71 W	20	

Note:

NE cor: Stone removed and Concrete Cor. post set in place  
Post 14 Dia Iron pin in post 1/2" O